# **Material Safety Data Sheet**

Concrete unit paving products including concrete pavers, precast concrete paving slabs, concrete grid pavers, and permeable interlocking concrete pavers

## **1**. Product and company identification

Common name Synonym	<ul> <li>Concrete unit paving products including concrete pavers, preca slabs, concrete grid pavers, and permeable interlocking concret</li> <li>Not available.</li> </ul>	st concrete paving e pavers
Code Material uses	<ul><li>Not available.</li><li>Not available.</li></ul>	
Supplier Manufacturer In case of emergency MSDS authored by:	<ul> <li>Not available.</li> <li>Not available.</li> <li>Not available.</li> <li>Kemika XXI Inc. + 1-450-435-7475 04/<sup>2</sup></li> </ul>	15/2006

## 2. Hazards identification

Physical state	: Solid.
Odor	: Odorless.
Color	: Various, depends on possible pigmentation.
Hazard status	: This material is classified hazardous under the WHMIS Controlled Product Regulation in Canada.
Emergency overview	: CAUTION!
	Dust from sawing or grinding: MAY CAUSE RESPIRATORY TRACT AND EYE IRRITATION.
	Risk of cancer depends on duration and level of exposure. Dry sawing or grinding of concrete masonry products may result in the release of respirable crystalline quartz. Prolonged exposure to respirable crystalline quartz may cause delayed (chronic) lung injury (silicosis). Acute or rapidly developing silicosis may occur in a short period of time in heavy exposure. Silicosis is a form of disabling pulmonary fibrosis, which can be progressive and may lead to death.
Routes of entry	: Eye contact. Inhalation. Ingestion.
Potential acute health effect	ts and the second se
Eyes	: May cause eye irritation.
Skin	: None, under normal conditions of uses. Unreacted cement can cause an exothermic reaction, resulting in a chemical skin burn if moisture is added.
Inhalation	: Dust from sawing or grinding: May cause respiratory tract irritation.
Ingestion	: No known significant effects or critical hazards.
Potential chronic health effects	<ul> <li>Carcinogenic effects Classified 1 (Known to be human carcinogens.) by NTP, + (Proven.) by NIOSH. Classified A2 (Suspected for humans.) by ACGIH, 2A (Probable for human.) by IARC [Silica, Crystalline - Quartz].</li> <li>Mutagenic effects Not available.</li> <li>Teratogenic effects: Not available.</li> </ul>
Medical conditions aggravated by over- exposure	: Repeated or prolonged exposure to the substance can produce lung damage. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged exposure to the substance can produce target organ damage. Pre-existing lung diseases such as emphysema or asthma: Pulmonary function may be reduced by inhalation of respirable crystalline silica. Also lung scarring produced by such inhalation may lead to a progressive massive fibrosis of the lung which may aggravate other pulmonary conditions and diseases and which increases susceptibility to pulmonary tuberculosis. Progressive massive fibrosis may be accompanied by right heart



Concrete unit paving products including concrete pavers, precast concrete paving slabs, concrete grid pavers, and permeable interlocking concrete pavers

enlargement, heart failure, and pulmonary failure. Smoking aggravates the effects of exposure.

See toxicological information (section 11)

3. Compositio	n/information on ingred	ients	
	Canada		
Name		CAS number	%
Silica, Crystalline - Quartz		14808-60-7	70 - 100
4. First aid me	easures		
Eye contact	: In case of contact, immediately flush medical attention if irritation develops	eyes with plenty of water for at s.	least 20 minutes
Skin contact	: Wash with soap and water. Get med	lical attention if symptoms occur	ſ.

- Inhalation
   : If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

   Ingestion
   : Do not induce vomiting. Never give anything by mouth to an unconscious person. Get
  - : Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

## 5. Fire-fighting measures

### **Extinguishing media**

Suitable	: Use an extinguishing agent suitable for the surrounding fire, since this material will not burn.
Not suitable	: None known.
Special exposure hazards	: No specific hazard.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment for surrounding fire.

## 6. Accidental release measures

Personal precautions	: Use suitable protective equipment.
Environmental precautions	: See section 13 for waste disposal information.
Methods for cleaning up	: Avoid creating dusty conditions and prevent wind dispersal. Dispose of according to all federal, state and local applicable regulations

## 7. Handling and storage

Handling

: Wash thoroughly after handling.

## 8. Exposure controls/personal protection

	Canada
Product name	Exposure limits
Silica, Crystalline - Quartz	ACGIH TLV (Canada, 1/2005).
	TWA: 0.05 mg/m <sup>3</sup> 8 hour(s). Form: Respirable fraction
	National Institute for Occupational Safety and Health (NIOSH).
	Recommended standard maximum permissible concentration is
	0.05 mg/m <sup>3</sup> (respirable free silica) as determined by a full-shift sample
	up to a 10-hour work day, 40-hour work week. See NIOSH Criteria for a
	Recommended Standard Occupational Exposure to Crystalline Silica.

Consult local authorities for acceptable exposure limits.



Concrete unit paving products including concrete pavers, precast concrete paving slabs, concrete grid pavers, and permeable interlocking concrete pavers		
Engineering measures	:	Use only with adequate ventilation. If user operations generate dust or fumes, use process enclosures, local exhaust ventilation or other engineering controls to keep worke exposure to airborne contaminants below any recommended or statutory limits.
Personal protection		
Eyes	1	Safety glasses.
Skin	1	Overall.
Respiratory	:	If respiratory protection is required, follow the requirements of the Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), or equivalent State standard. CSA standard for respirators is Z94.4-02 'selection, Use and Care of Respirators. Recommended: Dust respirator./Disposable particulate mask.
Hands	:	Leather gloves.
HMIS Code/Personal protective equipment	:	E
Personal protection in case of a large spill	e :	Not applicable. Follow good industrial hygiene practice.

## 9. Physical and chemical properties

Physical state	: Solid.
Color	: Various, depends on possible pigmentation.
Odor	: Odorless.
Molecular weight	: 60.09 g/mole
Molecular formula	: SiO <sub>2</sub>
Density	: 2250-2450 kg/m <sup>3</sup> .
Solubility	: Insoluble in cold water, hot water.

## 10. Stability and reactivity

Stability and reactivity	: The product is stable.
Incompatibility with various substances	: None known.
Hazardous decomposition products	: Not applicable.
Hazardous polymerization	: Will not occur.

## 11. Toxicological information

IDLH :	50 mg/m³
Acute Effects	
Eyes :	May cause eye irritation.
Skin :	None, under normal conditions of uses. Unreacted cement can cause an exothermic reaction, resulting in a chemical skin burn if moisture is added.
Inhalation :	Dust from sawing or grinding: May cause respiratory tract irritation.
Ingestion	No known significant effects or critical hazards.



Concrete unit paving products including concrete pavers, precast concrete paving slabs, concrete grid pavers, and permeable interlocking concrete pavers		
Potential chronic health effects	<ul> <li>Carcinogenic effects Classified 1 (Known to be human carcinogens.) by NTP, + (Proven.) by NIOSH. Classified A2 (Suspected for humans.) by ACGIH, 2A (Probable for human.) by IARC [Silica, Crystalline - Quartz].</li> <li>Mutagenic effects Not available.</li> <li>Teratogenic effects: Not available.</li> </ul>	

## 12. Ecological information

Environmental precautions	:	No known significant effects or critical hazards.
Products of degradation	÷	Some metallic oxides.
Toxicity of the products of biodegradation	:	The product itself and its products of degradation are not toxic.

### 13. Disposal considerations

Waste disposal

: Normal breakage may be picked up and discarded as common waste. Residue from dry sawing and grinding operations should be disposed of in accordance with federal, state and local applicable regulations.

## 14. Transport information

NAERG : Not applicable. Regulatory information

Regulatory information

UN/ IMDG/IATA/ TDG : Not regulated.

## 15. Regulatory information

### Canada

WHMIS (Canada)

: Not a WHMIS controlled material.



CEPA DSL: Concrete unit paving products including concrete pavers, precast concrete paving slabs, concrete grid pavers, and permeable interlocking concrete pavers

This product has been classified in accordance with the hazard criteria of the Canadian CPR. This MSDS contains all the information required by the CPR.

#### **International lists**

: This product, (and its ingredients) is (are) listed on national inventories, or is (are) exempted from being listed, Australia (AICS), in Europe (EINECS/ELINCS), in Korea (TCCL), in Japan (METI), in the Philippines (RA6969).

## 16. Other information

Hazardous Material : Information System (U.S.A.)	HMIS RATING			HAZARD RATINGS
	Health	*	1	4- Extreme
	Fire hazard		0	3- Serious 2- Moderate
	Physical Hazard		0	1- Slight
	Personal protection		E	U- Minimai See section 8 for more detailed information on personal protection

Page: 4/5

Concrete unit paving products including concrete pavers, precast concrete paving slabs, concrete grid pavers, and permeable interlocking concrete pavers				
National Fire Protection Association (U.S.A.)	: Health 1 0 Reactivity Special			
References	<ul> <li>ANSI Z400.1, MSDS Standard, 2004 Manufacturer's Material Safety Data Sheet Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2005.</li> </ul>			
Date of issue Version	: 04/15/2006 : 1			

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

